

8. REFERENCES

ABARE. 2001. Australian Forest and Wood Products Statistics, March and June quarters 2001. *ABARE*, Canberra, p. 13.

Alexiou, P.N. 1993. Accelerated Kiln-Drying and Drying Stresses in Regrowth Blackbutt *Eucalyptus Pilularis* Sm. *M. Sci. Thesis*, Australian National University, Australia, pp. 31-44, 57-75.

Alexiou, P., Marchant, J.F. and Shouyue, Z. 1989. Effect of Moisture Content and Density on the Viscoelastic Properties of *Eucalyptus pilularis* Sm. in Tension across the Grain. *IUFRO Wood Drying Conference*, Seattle, Washington, USA, pp. 71-78.

Andrews, M.K. and Muneri, A. 2002. CCT Blackbutt Trial – Between and Within tree Acoustic Results. Appendix B of CCT sawing Tech Report, *State Forests of NSW (Research and Development Division), Wood Quality Improvement Group (Queensland Forestry Research Institute)*. pp. 54-67.

Australian/New Zealand Standard™ AS/NZS 4787:2001. Timber – Assessment of Drying Quality, Standards Australia, Standards New Zealand, accessed March 12, 2003.

Bao, F.C., Jiang, Z.H., Jiang, X.M., Lu, X.X., Luo, X.Q. and Zhang. S.Y. 2001. Differences in Wood Properties between Juvenile Wood and Mature Wood in 10 Species grown in China. *Wood Science and Technology*. 35, pp. 363-375.

Becker, H.F. 1982. Acoustic Emissions during Wood Drying. *Holz Roh Werkstoff*. 40(9), pp. 345-350.

Boland, D.J., Booker, M.I.H., Chippendale, G.M., Hall, N., Hyland, B.P.M., Johnston, R.D., Kleinig, D.A. and Turner, J.D. 1989. Forest Trees of Australia, *CSIRO Melbourne*. <http://data.brs.gov.au/mapserv/plant/species.php?speciesid=14>. accessed 11/24/2003.

Booker, J. 1994. Improved Hardwood Timber Seasoning Productivity. *PhD Thesis*, Faculty of Engineering, University of Tasmania, Australia, pp. iv-ix, 46-64, 116-126.

Bramhall, G. 1979. Sorption Diffusion in Wood. *Wood Science*. 12(1), pp. 3-13.

Brooke, A.B. 1999. Optimisation of Hardwood Timber Drying Schedules. *M. Eng. (Research) Thesis*, University of Sydney, pp.21-41, 67-72.

Bodig, J. and Jayne, B.A. 1993. Mechanics of Wood and Wood Composites. *Krieger Publishing Company*, Malabar, Florida.

Burdon, R.D., Kibblewhite, R.P., Walker, J.C.F., Megraw, R.A., Evans, R., Cown, D.J. 2004. Juvenile Versus Mature Wood: A New Concept, Orthogonal to Corewood Versus Outerwood, with Special Reference to *Pinus radiata* and *P. taeda*. *Forest Science*, 50(4), 399-415.

Campbell, G.S. 1980. Index of Kiln Drying Schedules for Timber Dried in Australia. *Commonwealth Scientific and Industrial Research Organisation Building Research Division.*

Carlsson, P. and Tinnsten, M. 2002. Optimization of Drying Schedules Adapted for a Mixture of Boards with Distribution of Sapwood and Heartwood. *Drying Technology.* 20(2), pp. 403-418.

Caswell, T. 2005. Native Forestry is a way for wood. *The Australian Newspaper*, March 21, 2005, p. 30.

Cave, I.D. 1996. The Longitudinal Young's Modulus of *Pinus radiata*. *Wood Science and Technology.* 1(3), pp268-278.

Cave, I.D. and Walker, J.C.F. 1994. Stiffness of Wood in Fast-grown Plantation Softwoods: The Influence of Microfibril Angle. *Forest Products Journal.* 44(5), pp. 43-48.

Chafe, S.C., Barnacle, J.E., Hunter, A.J., Ilic, J., Northway, R.L., Rozsa, A.N. 1992. Collapse: An Introduction. *Division of Forest Products.* Commonwealth Scientific and Industrial Organization, Australia, pp. 1-8.

Choong, E.T. and Fogg, P.J. 1989. Differences in Moisture Content and Shrinkage between Innerwood and Outerwood of Two Shortleaf Pine Trees. *Forest Products Journal*. 39(3), pp. 13-18.

Cronin, K. 1997. Drying Lumber in Kilns: A Methodology for Stochastic Analysis using Markov Modelling. *Drying Technology*. 15(3&4), pp. 765-790.

Cronin, K., Abodayeh, K. and Caro-Corrales, J. 2002. Probabilistic Analysis and Design of the Industrial Timber Drying Process. *Drying Technology*. 20(2), pp. 307-324.

Cronin, K., Baucour, P., Abodayeh, K. and Barbot Da Silva., A. 2003. Probabilistic Analysis of Timber Drying Schedules. *Drying Technology*. 21(8), pp. 1433-1456.

Daudeville, L. 1999. Fracture in Spruce: Experiment and Numerical Analysis by Linear and Non-Linear Fracture Mechanics. *Holz Roh Werkstoff*. 57, pp. 425-432.

Dinwoodie, J.M. 2000. Timber: Its Nature and Behaviour. *E & FN Spom*. BRE, with the support of the Centre for Timber Technology and Construction at BRE, England.

Doe, P., Booker, J.R., Innes, T.C. and Oliver, A.R. 1996. Optimal Lumber Seasoning Using Acoustic Emission Sensing and Real Time Strain Modelling. *Proceedings Fifth IUFRO International Wood Drying Conference*, Quebec, Canada, pp. 209-220.

Doe, P.E. and Innes, T.C. 1999. Seasonability Determination from In-Log Property Measurements. *Proceedings Sixth IUFRO International Wood Drying Conference*, Stellenbosch, South Africa, pp. 117-120.

Doe, P.E., Oliver, A.R. and Booker, J.D. 1994. A Non-Linear Strain and Moisture Content Model of Variable Hardwood Drying Schedules. *Proceedings Fourth IUFRO International Wood Drying Conference*, Rotorua, New Zealand, pp. 203-210.

Evans, R. 1996. Research Updates from the CSIRO Division of Forestry and Forest Products: Onwood 12. <http://www.ffp.csiro.au/publicat/onwood/onwood12.htm>, accessed 2/7/2003.

Evans, R. and Ilic, J. 2001. Rapid Prediction of Wood Stiffness from Microfibril Angle and Density. *Forest Products Journal*. 51(3), pp. 53-57.

Evans, R., Kibblewhite, R.P. Stringer, S.L. 2001. Variation in Microfibril Angle, Density, and Fibre Orientation in Twenty-Nine *Eucalyptus nitens* Trees. *Appita Journal*, 53, pp. 450-457.

Evans, J.W., Senft, J.F. and Green, D.W. 2000. Juvenile Wood Effect in Red Alder: Analysis of Physical and Mechanical Data to Delineate Juvenile and Mature Wood Zones. *Forest Products Journal*. 50(7/8), pp 75-87.

Ferguson, I.S., Fox, J., Baker, T., Stackpole, D. and Wild, I. 2002. National and Regional Plantation Wood Availability 2001-2044. *Consultant's Report for National Forest Inventory, Bureau of Rural Sciences, Canberra.*

Fotsing, J.A.M., Tchagang, C.W. 2004. Experimental Determination of the Diffusion Coefficients of Wood in Isothermal Conditions. *African Journal of Physics* <http://www.physics.ncat.edu/michael/ajp> (accessed Nov 2004).

Haque, N. 2002. Modelling of Solar Kilns and the Development of an Optimised Schedule for Drying Hardwood Timber. *PhD Thesis.* The University of Sydney, Australia, pp. 78-79, 158.

Hewitt, G.F., Shires, G.L., Bott, T.R. 1994. Process Heat Transfer. *CRC Press, Florida,* p. 1024.

Honeycutt, R.M., Skaar, C. and Simpson, W.T. 1985. Use of Acoustic Emissions to Control Drying Rate of Red Oak. *Forest Products Journal.* 35(1), pp. 48-50.

Ilic, J. 2001. Variation of the Dynamic Elastic Modulus and Wave Velocity in the Fibre Direction with Other Properties during the Drying of *Eucalyptus regnans* F. Muell. *Wood Science and Technology.* 35, pp157-166.

Innes, T.C. 1995. Stress Model of a Wood Fibre in Relation to Collapse. *Wood Science and Technology*. 29, pp. 363-376.

Innes, T. 1996. Collapse and Internal Checking in the Latewood of *Eucalyptus regnans* F. Muell. *Wood Science and Technology*. 30, pp. 373-383.

Innes, T.C. and Redman, A.L. 2003. Comparative Drying Characteristics of Six Regrowth Australian Hardwoods, Proceedings Eight International IUFRO Wood Drying Conference, Brasov, Romania, Aug 24-29; International Union of Forest Research Organizations; pp. 101-105.

Johnson, I.G. and Nikles, D.G. 1996. Plan for Developing and Deploying Genetically-Improved Varieties of Blackbutt (*E.pilularis* Smith) in NSW. *State Forests of New South Wales Technical Paper*. Number 63, pp. 1-5.

Johnson, J.A. 1989. Stress Development. In *IUFRO 1989 Wood Drying Symposium, Appendix B*. IUFRO, Seattle, Washington.

Jönsson, J. and Thelandersson, S. 2003. The Effect of Moisture Gradients on Tensile Strength Perpendicular to Grain in Glulam. *Holz Roh Werkstoff*. 61, pp. 342-348.

Kärki, T. 2002. Drying Quality of European Aspen (*Populus tremula*) Timber. *Holz als Roh- und Werkstoff* 60: pp. 369-371.

Kayihan, F. 1993. Adaptive Control of Stochastic Batch Lumber Kilns. *Computers and Chemical Engineering*. 17(3), pp. 265-273.

Keey, R.B. 1992. Drying of Loose and Particulate Materials. *Hemisphere*, New York. p. 504.

Keey, R.B, Langrish. T.A.G. and Walker, J.C.F. 2000. Kiln Drying of Lumber. *Springer Verlag*, Berlin, pp. 65-115, 175-181.

Kibblewhite, R.P. and Riddell, M.J.C. 2001. Within-tree Variation of some Wood and Kraft Fibre Properties of *Eucalyptus fastigata* and *E. nitens*. *Appita Journal*, 54, pp. 136-143.

Kingston, R.S.T. and Risdon, C.J.E. 1961. Shrinkage and Density of Australian and other South-west Pacific Woods. Division of Forest Products Technological Paper No. 13. *Commonwealth Scientific and Industrial Organization*, Australia.

Kretschmann, D.E. and Green, D.W. 1996. Moisture Content-Specific Gravity relationships for Clear Southern Pine. *Proceedings of the International Wood Engineering Conference*, New Orleans, LA, pp. 28-31.

Langrish, T.A.G.; Brooke, A.S.; Davis, C.L., Musch, H.E; Barton, G.W. 1997. An Improved Drying Schedule for Australian Ironbark Timber: Optimization and Experimental Validation. *Drying Technology* 15(1), pp. 47-70.

Lewin, M. and Goldstein, I.S. 1991. Wood Structure and Composition. *Marcel Dekker, Inc*, New York, pp. 448-469.

Lichtenegger, H., Reiterer, A., Stanzl-Tschegg, S.E. and Fratzl, P. 1999. Variation of Cellulose Microfibril Angles in Softwoods and Hardwoods – A Possible Strategy of Mechanical Optimization. *Journal of Structural Biology*. 128, pp. 257-269.

Logan, J.D. 2003. Sensitivity to Fundamental Wood Properties in the Metriguard Model 7200 HCLT and the CLT. <http://www.metriguard.com/fiber.htm>, accessed 7/2/03.

Malaysian Timber Council (MTC). 2002a. Methods of Drying Wood in Air. <http://www.mtc.com.my/publication/library/drying/ch13.htm>, accessed 30/6/2004.

Malaysian Timber Council (MTC). 2002b. Glossary. <http://www.mtc.com.my/publication/library/drying/gloss.htm>, accessed 1/8/2004.

Malaysian Timber Council (MTC). 2002c. Staining and Discolouration. <http://www.mtc.com.my/publication/library/drying/ch46.htm>, accessed 4/4/2005.

McCurdy, M.; Pang, S.; Keey, R. 2003. Measurements of Colour Development in *Pinus radiata* Sapwood Boards During Drying at Various Schedules , Proceedings Eight International IUFRO Wood Drying Conference, Brasov, Romania, Aug 24-29; International Union of Forest Research Organizations. pp. 445-449.

Mills, R. 1991. Australian Timber Seasoning Manual. Australian Furniture Research and Development Institute Limited, pp. 160-166.

Noguchi, M., Kitayama, S., Satoyoshi, K. and Umetsu, J. 1987. Feedback Control for drying *Zelkova Serrata* Using In-Process Acoustic Emission Monitoring. *Forest Product Journal*. 37(1), pp. 28-34.

Oliver, A.R. 1991. A Model of the Behaviour of Wood as it Dries (With Special Reference to Eucalypt Materials). *Research Report CM91-1*. University of Tasmania, pp. 1-82.

Olson, S.M. 2003. The Wood Properties of New Zealand Silver Beech (*Nothofagus menziesii*), a Lesser-Known Hardwood Species. *Forest Products Journal*. 53(5), pp. 80-86.

Omarsson, S. 2000. A Numerical Study of the Shape Stability of Sawn Timber Subjected to Moisture Variation. *Wood Science and Technology*. 34, pp. 207-219.

Pangloss, W. 1993. Notes on Regression and Correlation. Comtea Ministry of Policy.

Poku, K, Wu, Q. and Vlosky, R. 2001. Wood Properties and their Variations within the Tree Stem of Lesser-Used Species of Tropical Hardwood from Ghana. *Wood and Fiber Science*. 33(2), pp 284-291.

Pordage, L. 2006.The Effects of Biological Variability on the Optimisation of Hardwood Drying Schedules. *PhD Thesis*. The University of Sydney, Australia, pp. 58-212.

Pordage, L.J. and Langrish, T.A.G. 2000. Optimization of Hardwood Drying Schedules Allowing for Biological Variability. *Drying Technology*. 18(8), pp. 1797-1815.

Plumptre, R.A. 1988. A Simple Guide to Timber Drying. *Reprinted from a United Nations Industrial Development Organization publication*. Oxford, U.K. pp. 13-15.

Queensland Department of Primary Industries and Fisheries. 2006. 09 Blackbutt., <http://www2.dpi.qld.gov.au/hardwoodsqld/7591.html>. accessed 12/12/2006.

Raymond, C.A. and Muneri, A. 2001.Nondestructive Sampling of *Eucalyptus globulus* and *E. nitens* for Wood Properties. I. Basic Density. *Wood Science and Technology*. 35, pp. 27-39.

Reiterer, A., Lichtenegger, H., Tschegg, S.E. and Fratzl, P. 1999. Experimental Evidence for a Mechanical Function of the Cellulose Spiral Angle in Wood Cell Walls. *Philos. Mag. A*. 79, pp2173-2186.

Ristea, C. and Maness, T.C. 2005. Analyzing the Distribution of Moisture Content in Kiln—Dried Lumber using Goodness of Fit Techniques—With Procedures. *Journal of the Institute of Wood Science*. 17:1(97), pp. 11—23.

Salin, J.G. 1992. Numerical Prediction of Checking During Timber Drying and a New Mechano-Sorptive Creep Model. *Holz Roh Werkstoff*. 50, pp. 195-200.

Salin, J.G. 2001. Analysis and Optimization of the Conditioning Phase in Timber Drying. *Drying Technology*. 19(8), pp. 1711-1724.

Schaffner, R.D. 1981. Fundamental Aspects of Timber Seasoning, *M.Eng.Sci. Thesis*, Faculty of Engineering Science, Faculty of Engineering, University of Tasmania, Australia, pp. 130-135.

Shapiro, S.S. and Wilk, M.B. 1965. An Analysis of Variance Test for Normality Complete Samples. *Biometrika*. 52(3 and 4), pp. 591—611.

Shupe, T.F., Choong, E.T. and Gibson, M.D. 1995a. Differences in Moisture Content and Shrinkage between Outerwood, Middlewood, and Corewood of Two Yellow-Poplar Trees. *Forest Products Journal*. 45(9), pp. 85-90.

Shupe, T.F., Choong, E.T. and Gibson, M.D. 1995b. Differences in Moisture Content and Shrinkage between Innerwood and Outerwood of a Single Cottonwood Tree. *Forest Products Journal*. 45(10), pp. 89-92.

Siau, J.F. 1984. *Transport Processes in Wood*. Springer Verlag, New York, p. 25.

Smith, L.I. 2002. A Tutorial on Principal Components Analysis. http://www.cs.otago.ac.nz/cosc453/student_tutorials/principal_components.pdf (accessed March 2004)

Spiegel, M.R.; Stephens, L.J. 1999. Chapter 6 – Elementary Probability Theory and Chapter 7 –The Binomial, Normal, and Poisson Distributions; Chapter 7 – Statistical Decision Theory. In *Schaum's Outlines: Statistics*, Third Edition; McGraw—Hill: Singapore, pp. 130—131, 156, 216—264.

Steinmann, D.E. 1995. Real-Time Simulation of Solar Kiln Drying of Timber. *Solar Energy*. 54(5), pp. 309-315.

Swett, T.M. and Milota, M.R. 1999. Drying Lumber of Submerchantable Length. *Forest Products Journal*. 49(4), pp. 71-76.

Walker, J.C.F. 1993. Primary Wood Processing. *Chapman & Hall*, London, pp. 68-74.

Wan, J. and Langrish, T.A.G. 1995. A Numerical Simulation for Solving the Diffusion Equations in the Drying of Hardwood Timber. *Drying Technology*, 13(3), pp. 783-800.

Wimmer, R. 2000. Wood Quality - Causes, Methods, Control. <http://www.boku.ac.at/botanik/wood/woodquality/Chapter4.pdf>, accessed 15/08/2003.

Wu, Q. 1989. An Investigation of Some Problems in Drying of Tasmanian Eucalypt Timbers. *M.Eng.Sci. Thesis*, University of Tasmania, Hobart, pp. 140-141

Yang, J.L. and Evans, R. 2003. Prediction of MOE of Eucalypt Wood from Microfibril Angle and Density. *Holz Roh Werkstoff*. 61, pp. 449-452.

Zhang, S.Y. and Zhong, Y. 1992. Structure-Property Relationship of Eood in East-Liaoning Oak. *Wood Science and Technology*. 26, pp. 139-149.